







This is a multi-purpose lightweight lubricant that both penetrates and protects against rust and corrosion. Displaces moisture/dust/scale, prevents flash rusting, and provides long term protection for metal. Does not contain silicone.

Suggested Uses:

Protect metals from salt, corrosion, moisture Lubricate hinges, threads, and bushings Loosen frozen nuts, bolts, and fasteners Coating metal components

Packaging:

UPC Code 043281009379

Cans per case 6 Shipping weight per case 9 lbs.

Container 16 fluid ounce can
Label weight 12 ounces (340 grams)
Shipping Classification limited quantity, UN 1950

Hazard Class 2.1

Properties:

Coverage Up to 12 square feet
Cleanup Lacquer thinner
Storage Temperature 40-100F

Storage Temperature 40-100F Application Temperature 50-90F

Flammability Extremely Flammable

Flash point -4F Specific Gravity 0.75 Solids Content 28%

VOC content 49%, can't exceed 50%

HAPs Content 18%
Lubricity Rating Excellent
Appearance Clear
Weather Resistance Excellent
Operating Speed 2000+ RPM
High Temperature Resistence 150F

High Temperature Resistence 150F Low Temperature Resistence - 20F Heavy Load Capability No Shelf life Guaranteed for 2 years

12-2-2021

