## 1 Identification of the substance and manufacturer

Trade name: Product code: Recommended use: Uses advised against: Manufacturer/Supplier: Emergency telephone number:	DOVE GRAY 0000980027 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com 1-800-255-3924	Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com	
2 Hazard(s) identification			
Classification of the substance or m	ivturo		
Flammable Aerosols 1			
	H222 Extremely flammable aerosol.	wolede if bested	
Gases under Pressure - Liquefied gas	H280 Contains gas under pressure; may e H319 Causes serious eye irritation.	spioue il fieateu.	
Eye Irritation 2A Carcinogenicity 2	H351 Suspected of causing cancer. Route	of exposure: Inhalation	
Toxic to Reproduction 1B	H360 May damage fertility or the unborn c		
Specific Target Organ Toxicity - Single		ind.	
	ted Exposure 2 H373 May cause damage to organs throug	ah prolonged or repeated exposure.	
Additional information:			
GHS Hazard pictograms	$\land \land \land \land$		
	GHS02 GHS04 GHS07 GHS08		
Signal word	Danger		
Hazard statements	Extremely flammable aerosol.		
	Contains gas under pressure; may explode if heated.		
	Causes serious eye irritation. Suspected of causing cancer. Route of exposure: Inhalation	n	
	May damage fertility or the unborn child.	511.	
	May cause drowsiness or dizziness.		
Precautionary statements	May cause damage to organs through prolonged or repea Obtain special instructions before use.	ted exposure.	
Frecautionary statements	Keep away from heat/sparks/open flames/hot surfaces I	No smokina.	
	Do not spray on an open flame or other ignition source.	-	
	Pressurized container: Do not pierce or burn, even after use.		
	Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.		
	Use only outdoors or in a well-ventilated area.		
	Wear protective gloves/protective clothing/eye protection/	face protection.	
	IF INHALED: Remove person to fresh air and keep comfo If in eyes: Rinse cautiously with water for several minute	Rable for breathing.	
	easy to do. Continue rinsing.	s. Remove contact lenses, in present and	
	Call a poison center/doctor if you feel unwell.		
	If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place.		
	Store in a well-ventilated place. Store locked up.		
	Protect from sunlight. Do not expose to temperatures exce	eeding 50°C/122°F.	
	Dispose of contents/container in accordance with local/reg	gional/national/international regulations.	
2 Composition/information on inc	radianta		
3 Composition/information on ing	realents		

## on/information on ingre nho

<b>Chemical Description:</b> This product is a mixture of the substances listed below with nonhazardous additions.			
Dangerous	components:		
67-64-1	Acetone		25-50%
	propane		15-25%
64742-89-8	VM&P Naphtha		10-15%
106-97-8	n-butane		10-15%
64742-47-8	Mineral Spirits		5-10%
108-88-3	Toluene		1-5%
13463-67-7	titanium dioxide		1-5%
67-63-0	Isopropyl Alcohol		1-5%

- **4 First-aid measures** 
  - After inhalation: After skin contact: After eye contact:

Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 2)

Safety Data Sheet

Printing date 01/17/2024

Revised On 01/17/2024

	(Contd. of page
After swallowing:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness
Indication of any immediate medi attention needed:	
attention needed.	
Fire-fighting measures	
Extinguishing agents: Special hazards:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.
Protective equipment for	
firefighters:	A respiratory protective device may be necessary.
Accidental release measures	
Personal precautions, protective equipment and emergency	
procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up:	Ensure adequate ventilation.
	Dispose contaminated material as waste according to section 13.
' Handling and storage	
Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up.
Long-term value: 250 p A4, BEI	pm
74-98-6 propane PEL (USA) Long-term value: 1800	
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima	mg/m³, 1000 ppm
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8n-butane	mg/m³, 1000 ppm I oxygen content ( D, EX)
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima	mg/m³, 1000 ppm I oxygen content ( D, EX) mg/m³, 800 ppm
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)108-88-3 Toluene	mg/m³, 1000 ppm I oxygen content ( D, EX) mg/m³, 800 ppm ppm
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)108-88-3 ToluenePEL (USA)Long-term value: 200 pCeiling limit value: 300;	mg/m³, 1000 ppm I oxygen content ( D, EX) mg/m³, 800 ppm ppm pm 500* ppm
PEL (USA) Long-term value: 1800   REL (USA) Long-term value: 1800   TLV (USA) see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA)   REL (USA) Long-term value: 1900   TLV (USA) Short-term value: 1000 (EX) <b>108-88-3 Toluene</b> PEL (USA)   PEL (USA) Long-term value: 200 p   Ceiling limit value: 300; *10-min peak per 8-hr s   REL (USA) Short-term value: 300 r	mg/m <sup>3</sup> , 1000 ppm I oxygen content ( D, EX) mg/m <sup>3</sup> , 800 ppm ppm pm 500* ppm shift ng/m <sup>3</sup> , 150 ppm
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)(EX) <b>108-88-3 Toluene</b> PEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 560 m Long-term value: 375 m	mg/m <sup>3</sup> , 1000 ppm I oxygen content ( D, EX) mg/m <sup>3</sup> , 800 ppm ppm 500* ppm shift ng/m <sup>3</sup> , 150 ppm ng/m <sup>3</sup> , 150 ppm
PEL (USA) Long-term value: 1800   REL (USA) Long-term value: 1800   TLV (USA) see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA) Long-term value: 1900   TLV (USA) Short-term value: 1900   TLV (USA) Short-term value: 1000 (EX) <b>108-88-3 Toluene</b> PEL (USA)   PEL (USA) Long-term value: 200 p   Ceiling limit value: 300; *10-min peak per 8-hr s   REL (USA) Short-term value: 560 n	mg/m <sup>3</sup> , 1000 ppm I oxygen content ( D, EX) mg/m <sup>3</sup> , 800 ppm ppm 500* ppm shift ng/m <sup>3</sup> , 150 ppm ng/m <sup>3</sup> , 150 ppm
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)108-88-3 ToluenePEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Isopropyl Alcohol	mg/m <sup>3</sup> , 1000 ppm I oxygen content ( D, EX) mg/m <sup>3</sup> , 800 ppm ppm 500* ppm shift ng/m <sup>3</sup> , 150 ppm ng/m <sup>3</sup> , 100 ppm m
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)Short-term value: 200 pCeiling limit value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300 rREL (USA)Short-term value: 300 rTLV (USA)Short-term value: 300 rTLV (USA)Long-term value: 375 rrTLV (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 rrREL (USA)Short-term value: 980 rrREL (USA)Short-term value: 1225	mg/m <sup>3</sup> , 1000 ppm l oxygen content ( D, EX) mg/m <sup>3</sup> , 800 ppm ppm 500* ppm shift ng/m <sup>3</sup> , 150 ppm ng/m <sup>3</sup> , 100 ppm m
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1900TLV (USA)Short-term value: 200 p(EX)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300 rREL (USA)Short-term value: 300 rTLV (USA)Short-term value: 300 rBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 rREL (USA)Short-term value: 980 rREL (USA)Short-term value: 980 r	mg/m³, 1000 ppm I oxygen content ( D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm ng/m³, 100 ppm m
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)Short-term value: 200 pCeiling limit value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300 rREL (USA)Short-term value: 300 rTLV (USA)Short-term value: 300 rTLV (USA)Long-term value: 375 rrTLV (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 rrREL (USA)Short-term value: 980 rrREL (USA)Short-term value: 1225	mg/m <sup>3</sup> , 1000 ppm l oxygen content ( D, EX) mg/m <sup>3</sup> , 800 ppm ppm 500* ppm shift ng/m <sup>3</sup> , 150 ppm m m ng/m <sup>3</sup> , 100 ppm m mg/m <sup>3</sup> , 500 ppm ng/m <sup>3</sup> , 500 ppm ng/m <sup>3</sup> , 400 ppm
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)(EX) <b>108-88-3 Toluene</b> PEL (USA)PEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 560 m Long-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A4 <b>67-63-0 Isopropyl Alcohol</b> PEL (USA)Long-term value: 980 m REL (USA)REL (USA)Short-term value: 980 m Short-term value: 200 pBEI, A4Ingredients with biological limit v	mg/m³, 1000 ppm I oxygen content ( D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm ng/m³, 150 ppm m m
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)(EX) <b>108-88-3 Toluene</b> PEL (USA)PEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 980 mTLV (USA)Short-term value: 200 pBEI, A4Ingredients with biological limit vIngredients with biological limit v	mg/m³, 1000 ppm I oxygen content ( D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm ng/m³, 150 ppm m m
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)(EX) <b>108-88-3 Toluene</b> PEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300 rTLV (USA)Short-term value: 300 rPEL (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 1225 Long-term value: 980 mTLV (USA)Short-term value: 200 pBEI, A4Ingredients with biological limit v67-64-1 AcetoneBEI (USA)BEI (USA)25 mg/L Medium: urine	mg/m³, 1000 ppm I oxygen content ( D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm ng/m³, 150 ppm m m
PEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima <b>106-97-8 n-butane</b> REL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)(EX) <b>108-88-3 Toluene</b> PEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A4 <b>67-63-0 Isopropyl Alcohol</b> PEL (USA)Long-term value: 980 mREL (USA)Short-term value: 1225 Long-term value: 980 mTLV (USA)Short-term value: 200 pBEI, A4Ingredients with biological limit v <b>67-64-1 Acetone</b> BEI (USA)BEI (USA)25 mg/L	mg/m³, 1000 ppm I oxygen content ( D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm ng/m³, 150 ppm m m mg/m³, 400 ppm mg/m³, 500 ppm ng/m³, 400 ppm ppm pm

Printing date 01/17/2024

F

Revised On 01/17/2024

## Trade name: DOVE GRAY

	_	(Contd. of page 2)	
108-88-3 T			
BEI (USA)	N) 0.02 mg/L Medium: blood		
	Medium: blood Time: prior to last shift of workweek		
	Parameter: Toluene		
	0.03 mg/L		
	Medium: urine		
	Time: end of shift		
	Parameter: Toluene		
	0.3 mg/g creatinine		
	Medium: urine		
	Time: end of shift		
	Parameter: o-Cresol with hy	varoiysis (background)	
	propyl Alcohol		
BEI (USA)	40 mg/L Medium: urine		
	Time: end of shift at end of	workweek	
	Parameter: Acetone (backg		
Hygienic p	、	Keep away from foodstuffs and animal feed. Wash hands after use.	
, g.oo p		Immediately remove all soiled and contaminated clothing.	
		Wash hands after use.	
		Store protective clothing separately.	
		Avoid contact with the eyes and skin. Do not eat or drink while working.	
Breathing	equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In	
		cases where short and/or long term overexposure exists, a NIOSH approved respirator should be	
		worn. If you suspect overexposure conditions exist, please consult an authority on chemical	
		hygiene.	
Hand prote	ection:	Nitrile gloves.	
Eye protection:The glove material must be impermeable and resistant to the substance.Tightly sealed goggles		Tightly sealed goggles	
9 Physical	and chemical properties		
Appearance	e:	Aerosol.	
Odor:		Aromatic	
Odor three	snold:	Not determined.	
pH-value:		Not determined.	
	oint/Melting range	Undetermined.	
Boiling po		-44 °C (-47.2 °F)	
Flash poin	t:	-19 °C (-2.2 °F)	
	ity (solid, gas):	Extremely flammable.	
Decompos	sition temperature:	Not determined.	
Auto igniti	na:	Product is not self-igniting.	
	explosion:	In use, may form flammable/explosive vapour-air mixture.	
	losion Limit:	1.7 Vol %	
Upper Exp	losion Limit:	10.9 Vol %	
Vapor pres		Not determined.	
Relative D		Between 0.77 and 0.85 (Water equals 1.00)	
Vapor den		Not determined.	
Evaporatio	on rate	Not applicable.	
Partition c	oefficient: n-octonal/water	: Not determined.	
Solubility:		Not determined.	
Viscosity:		Not determined.	
Water:		0.0 %	
10 Stability	and reportivity		
	and reactivity	Ctable at normal temperatures	
Reactivity: Conditions	s to avoid:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing	
Conditions		temperatures.	
Chemical s	stability:	Not fully evaluated.	
Possibility	of hazardous reactions:	No dangerous reactions known.	
Incompatil	ble materials:	No further relevant information available.	
Hazardous	decomposition:	No dangerous decomposition products known.	

Safety Data Sheet

Trade name: DOVE GRAY

Printing date 01/17/2024

Revised On 01/17/2024

Page 4/5

	(Contd. of page 3)	
11 Toxicological information		
LD/LC50 values that are relevant for	classification:	
13463-67-7 titanium dioxide		
Oral LD50 >20,000 mg/kg (rat)		
Dermal LD50 >10,000 mg/kg (		
Inhalative LC50/4 h >6.82 mg/l (rat)		
67-63-0 Isopropyl Alcohol		
Oral LD50 4,570 mg/kg (rat		
Dermal LD50 13,400 mg/kg (rat		
Inhalative LC50/4 h 30 mg/l (rat)		
Information on toxicological effects	· No data available	
Skin effects:	No irritant effect.	
Eye effects:	Irritating effect.	
Sensitization:	No sensitizing effects known.	
12 Ecological information		
Aquatic toxicity:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes.	
Persistence and degradability: Other information:	This product does not contain any chlorofluorocarbons (CEC's) bydrochlorofluorocarbons	
	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated	
	solvents.	
Bioaccumulative potential:	No further relevant information available.	
Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available.	
Other adverse effects.		
13 Disposal considerations		
	tate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be	
disposed of responsibly. Do not heat of	r cut empty containers with electric or gas torches.	
Recommendation:	Completely empty cans should be recycled.	
Recommended cleansing agent:	Water, if necessary with cleansing agents.	
14 Transport information		
UN-Number	UN1950	
DOT	ŪN1950	
DOT	Aerosols, flammable	
ADR	1950 Aerosols	
Transport hazard class(es): Class	2.1 Gases	
Marine pollutant:	No	
Special precautions for user:	Warning: Gases	
EMS Number:	F-D,S-U	
Packaging Group:		
UN "Model Regulation":	UN1950, Aerosols, 2.1	
15 Regulatory information		
SARA Section 355 (extremely hazar	dous substances):	
None of the ingredients in this product		
SARA Section 313 (Specific toxic ch		
108-88-3 Toluene	······································	
67-63-0 Isopropyl Alcohol		
Toxic Substances Control Act		
(TSCA):	All hazardous ingredients are found on the inventory list of substances.	
Canadian Domestic Substances Lis	t · · ·	
(DSL): Consumer Product Safety	All ingredients are listed or exempted.	
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.	
California Proposition 65 chemicals		
13463-67-7 titanium dioxide		
100-41-4 ethyl benzene		
1333-86-4 Carbon black		
Prop 65 chemicals known to cause	birth defects or reproductive harm:	
108-88-3 Toluene		
	(Contd. on page 5	

Printing date 01/17/2024	Revised On 01/17/2024
Trade name: DOVE GRAY	
	(Contd. of page 4)
EPA:	
67-64-1 Acetone	
4C Other information	

**16 Other information** 

Contact:

Regulatory Affairs