# 1 Identification of the substance and manufacturer

Trade name: Product code: Recommended use: Uses advised against: Manufacturer/Supplier: Emergency telephone number:	CUMMINS BEIGEEN00730000Paint and coatings application.Any that differs from the recommended use.Seymour of Sycamore917 Crosby AvenueSycamore, IL 60178 USAphone: 815-895-9101www.seymourpaint.com1-800-255-3924	
2 Hazard(s) identification		
Classification of the substance or m	ixture	
Flammable Aerosols 1	H222 Extremely flammable aerosol.	
Gases under Pressure - Liquefied gas	H280 Contains gas under pressure; may explode if heated.	
Eye Irritation 2A	H319 Causes serious eve irritation.	
Carcinogenicity 2	H351 Suspected of causing cancer. Route of exposure: Inhalation.	
Specific Target Organ Toxicity - Single		
	ted Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.	
Additional information:		
GHS Hazard pictograms	$\land \land \land \land$	
	GHS02 GHS04 GHS07 GHS08	
Signal word	Danger	
Hazard statements	Extremely flammable aerosol. Contains gas under pressure; may explode if heated.	
	Causes serious eye irritation.	
	Suspected of causing cancer. Route of exposure: Inhalation.	
	May cause drowsiness or dizziness.	
	May cause damage to organs through prolonged or repeated exposure.	
Precautionary statements	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces No smoking.	
	Do not spray on an open flame or other ignition source.	
	Pressurized container: Do not pierce or burn, even after use.	
	Do not breathe dust/fume/gas/mist/vapors/spray.	
	Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.	
	Wear protective gloves/protective clothing/eye protection/face protection.	
	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and	
	easy to do. Continue rinsing.	
	Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.	
	Store in a well-ventilated place.	
	Store locked up.	
	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
	Dispose of contents/container in accordance with local/regional/national/international regulations.	

3 Composition/information on ingredients			
Chemical c Chemical D	haracterization: Mixtures escription:	This product is a mixture of the substances listed below with nonhazardous additions.	
Dangerous components:			
67-64-1	Acetone		25-50%
74-98-6	propane		15-25%
106-97-8	n-butane		5-10%
110-19-0	Isobutyl Acetate		5-10%
13463-67-7	titanium dioxide		1-5%
108-10-1	methyl isobutyl ketone		1-5%
1317-65-3	Calcium Carbonate		1-5%
108-65-6	PM acetate		1-5%
107-87-9	Methyl Propyl Ketone		1-5%
2807-30-9	Glycol Ether EP		1-5%

## **4 First-aid measures**

After inhalation: After skin contact: After eye contact: Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 2) Safety Data Sheet

Printing date 01/10/2024

Revised On 01/10/2024

Printing date 01/10/2024	Printing date 01/10/2024 Revised On 01/10/2024		
Trade name: CUMMINS BEIGE			
<b>A</b> <i>f</i> 4a <i>n</i> annall i	din au	Pince out mouth and then drink plents of water (Contd. of page 1)	
After swallow	ving:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.	
Most importa	ant symptoms and	Tanse moduli wati water. Do not induce volmany.	
effects:		Dizziness	
Indication of	any immediate medical		
attention nee	ded:	No further relevant information available.	
5 Fire-fighting	g measures		
Extinguishing	g agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.	
Special hazai		Can form explosive gas-air mixtures.	
Protective eq firefighters:	uipment for	A respiratory protective device may be necessary.	
menginters.			
	elease measures		
Personal pre	cautions, protective		
	nd emergency	Wear protective equipment. Keep upprotected persons away	
procedures:		Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.	
Methods and	material for	Use respiratory protective device against the enects of functs/destractorsol.	
	and cleaning up:	Ensure adequate ventilation.	
7 Handling an	nd storage		
	for safe handling	Use only in well ventilated areas.	
Storage requ	irements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.	
otorage requ	li ellients.	Store locked up.	
		·	
	antrala/naraanal arat	action	
•	ontrols/personal prot		
		equire monitoring at the workplace:	
67-64-1 Aceto			
	Long-term value: 2400 n		
` '	Long-term value: 590 mg		
TLV (USA)	Short-term value: 500 pp	om	
	Long-term value: 250 pp A4, BEI	m	
	-		
74-98-6 propa		ag/m <sup>3</sup> 1000 mm	
	Long-term value: 1800 n		
	Long-term value: 1800 n		
	see Appendix F Minimal	oxygen content ( D, EX)	
106-97-8 n-bu		1 2 000	
	Long-term value: 1900 n		
	Short-term value: 1000 p	ppm	
110-19-0 Isob	(EX)		
	Long-term value: 700 mg	a/m³ 150 ppm	
	Long-term value: 700 mg		
TLV (USA)	Short-term value: 150 pp		
1LV (USA)			
1	Long-term value: 50 ppp		
108-10-1 mot	Long-term value: 50 ppn	•	
	hyl isobutyl ketone		
PEL (USA)	hyl isobutyl ketone Long-term value: 410 mg	g/m³, 100 ppm	
	<b>hyl isobutyl ketone</b> Long-term value: 410 mg Short-term value: 300 m	g/m³, 100 ppm g/m³, 75 ppm	
PEL (USA) REL (USA)	<b>hyl isobutyl ketone</b> Long-term value: 410 m Short-term value: 300 m Long-term value: 205 m	g/m³, 100 ppm g/m³, 75 ppm g/m³, 50 ppm	
PEL (USA)	hyl isobutyl ketone Long-term value: 410 m Short-term value: 300 m Long-term value: 205 m Short-term value: 75 ppr Long-term value: 20 ppn	g/m³, 100 ppm g/m³, 75 ppm g/m³, 50 ppm n	
PEL (USA) REL (USA)	<b>hyl isobutyl ketone</b> Long-term value: 410 m Short-term value: 300 m Long-term value: 205 m	g/m³, 100 ppm g/m³, 75 ppm g/m³, 50 ppm n	
PEL (USA) REL (USA)	hyl isobutyl ketone Long-term value: 410 mg Short-term value: 300 m Long-term value: 205 mg Short-term value: 75 ppr Long-term value: 20 ppn BEI, A3	g/m³, 100 ppm g/m³, 75 ppm g/m³, 50 ppm n	
PEL (USA) REL (USA) TLV (USA) <b>108-65-6 PM</b>	hyl isobutyl ketone Long-term value: 410 mg Short-term value: 300 m Long-term value: 205 mg Short-term value: 75 ppr Long-term value: 20 ppn BEI, A3	g/m³, 100 ppm g/m³, 75 ppm g/m³, 50 ppm n n	
PEL (USA) REL (USA) TLV (USA) <b>108-65-6 PM</b> WEEL (USA)	hyl isobutyl ketone Long-term value: 410 mg Short-term value: 300 m Long-term value: 205 mg Short-term value: 75 ppr Long-term value: 20 ppn BEI, A3 acetate Long-term value: 50 ppn	g/m³, 100 ppm g/m³, 75 ppm g/m³, 50 ppm n n	
PEL (USA) REL (USA) TLV (USA) 108-65-6 PM WEEL (USA) 107-87-9 Met	hyl isobutyl ketone Long-term value: 410 mg Short-term value: 300 m Long-term value: 205 mg Short-term value: 75 ppr Long-term value: 20 ppn BEI, A3 acetate Long-term value: 50 ppn hyl Propyl Ketone	g/m³, 100 ppm g/m³, 75 ppm g/m³, 50 ppm n n	
PEL (USA) REL (USA) TLV (USA) <b>108-65-6 PM</b> WEEL (USA) <b>107-87-9 Met</b> PEL (USA)	hyl isobutyl ketone Long-term value: 410 mg Short-term value: 300 m Long-term value: 205 mg Short-term value: 75 ppr Long-term value: 20 ppn BEI, A3 acetate Long-term value: 50 ppn hyl Propyl Ketone Long-term value: 700 mg	g/m³, 100 ppm g/m³, 75 ppm g/m³, 50 ppm n n	
PEL (USA) REL (USA) TLV (USA) <b>108-65-6 PM</b> WEEL (USA) <b>107-87-9 Met</b> PEL (USA) REL (USA)	hyl isobutyl ketone Long-term value: 410 mg Short-term value: 300 m Long-term value: 205 mg Short-term value: 75 ppr Long-term value: 20 ppn BEI, A3 acetate Long-term value: 50 ppn hyl Propyl Ketone Long-term value: 700 mg Long-term value: 530 mg	g/m³, 100 ppm g/m³, 75 ppm n n n g/m³, 200 ppm g/m³, 150 ppm	
PEL (USA) REL (USA) TLV (USA) <b>108-65-6 PM</b> WEEL (USA) <b>107-87-9 Met</b> PEL (USA) REL (USA)	hyl isobutyl ketone Long-term value: 410 mg Short-term value: 300 m Long-term value: 205 mg Short-term value: 75 ppr Long-term value: 20 ppn BEI, A3 acetate Long-term value: 50 ppn hyl Propyl Ketone Long-term value: 700 mg	g/m³, 100 ppm g/m³, 75 ppm n n n g/m³, 200 ppm g/m³, 150 ppm	

Revised On 01/10/2024

#### Trade name: CUMMINS BEIGE

	(Contd. of page 2)		
Ingredients with biological limit	values:		
67-64-1 Acetone			
Medium: urine Time: end of shift			
108-10-1 methyl isobutyl ketone			
BEI (USA) 1 mg/L Medium: urine Time: end of shift Parameter: MIBK			
Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.		
Breathing equipment: Hand protection:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene. Nitrile gloves.		
Eye protection:	The glove material must be impermeable and resistant to the substance. Tightly sealed goggles		
9 Physical and chemical proper	ties		
Appearance: Odor: Odor threshold:	Aerosol. Aromatic Not determined.		
pH-value: Melting point/Melting range Boiling point:	Not determined. Undetermined. -110 °C (-166 °F)		
Flash point: Flammability (solid, gas):	-19 °C (-2.2 °F) Extremely flammable.		

Auto igniting:

Danger of explosion: Lower Explosion Limit: Upper Explosion Limit:

**Decomposition temperature:** 

1.7 Vol % 10.9 Vol % Vapor pressure: Not determined. Relative Density: Vapor density Between 0.77 and 0.85 (Water equals 1.00) Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined. Water: 0.0 %

Not determined.

Product is not self-igniting.

### **10 Stability and reactivity**

Reactivity: Conditions to avoid: Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. Not fully evaluated. Chemical stability: No dangerous reactions known. Possibility of hazardous reactions: Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

In use, may form flammable/explosive vapour-air mixture.

## **11 Toxicological information**

LD/LC50 v	LD/LC50 values that are relevant for classification:			
110-19-0 Isobutyl Acetate				
Oral	LD50	50 4,763 mg/kg (rbt)		
13463-67-	13463-67-7 titanium dioxide			
Oral	LD50	>20,000 mg/kg (rat)		
Dermal	LD50	>10,000 mg/kg (rbt)		
Inhalative	LC50/4 h	>6.82 mg/l (rat)		

(Contd. on page 4)

Revised On 01/10/2024

Page 4/5

Trade name: CUMMINS BEIGE	
108-10-1 methyl isobutyl ketone	(Contd. of page 3)
Oral LD50 2,100 mg/kg (rat	
Dermal LD50 16,000 mg/kg (ra	
Inhalative LC50/4 h 11 mg/l (ATE)	
8.3-16.6 mg/l (ra	t)
108-65-6 PM acetate	
Oral LD50 8,500 mg/kg (rat	
Inhalative LC50/4 h 35.7 mg/l (rat)	
Information on toxicological effects	: No data available.
Skin effects:	No irritant effect.
Eye effects:	Irritating effect.
Sensitization:	No sensitizing effects known.
12 Ecological information	
Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability: Other information:	The product is degradable after prolonged exposure to natural weathering processes.
Other mormation:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated
	solvents.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Other adverse effects:	No further relevant information available.
13 Disposal considerations	
Dispose of in accordance with local, s	tate, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be
	or cut empty containers with electric or gas torches.
Recommendation: Recommended cleansing agent:	Completely empty cans should be recycled. Water, if necessary with cleansing agents.
Recommended creatising agent.	
14 Transport information	
14 Transport information	
UN-Number DOT	UN1950 UN1950
DOT	Aerosols, flammable
ADR	1950 Aerosols
Transport hazard class(es):	
Class	2.1 Gases
Marine pollutant: Special precautions for user:	No Warning: Gases
EMS Number:	F-D,S-U
Packaging Group:	
UN "Model Regulation":	UN1950, Aerosols, 2.1
15 Regulatory information	
SARA Section 355 (extremely hazar	dous substances):
None of the ingredients in this product	
SARA Section 313 (Specific toxic cl	
108-10-1 methyl isobutyl ketone	
Toxic Substances Control Act	
(TSCA):	All hazardous ingredients are found on the inventory list of substances.
Canadian Domestic Substances Lis	t · · ·
(DSL):	All ingredients are listed or exempted.
Consumer Product Safety	This product complice with 16 CED 1202 and does not contain more than 00 mm of load
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemicals	
108-10-1 methyl isobutyl ketone	
100-41-4 ethyl benzene 1333-86-4 Carbon black	
Prop 65 chemicals known to cause	birth defects or reproductive harm:
108-10-1 methyl isobutyl ketone	
EPA:	
67-64-1 Acetone	
	1
110-19-0 Isobutyl Acetate	l D

Trade name: CUMMINS BEI	GE	
108-10-1 methyl isobut	tyl ketone	(Contd. of page 4)
16 Other information		
Contact:	Regulatory Affairs	