Printing date 01/25/2024 Revised On 01/25/2024

1 Identification of the substance and manufacturer

Trade name: **SAFETY GREEN (SOLVENT)**

0000200955 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated. Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**







Signal word Danger

Extremely flammable aerosol. **Hazard statements**

Contains gas under pressure; may explode if heated. Suspected of causing cancer. Route of exposure: Inhalation. May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use. **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
	Calcium Carbonate	≥20-≤25%
64742-89-8	VM&P Naphtha	15-25%
74-98-6	propane	15-25%
106-97-8	n-butane	5-10%
142-82-5		≥5-<10%
	Mineral Spirits	5-10%
67-63-0	Isopropyl Alcohol	1-5%

4 First-aid measures

Supply fresh air; consult doctor in case of complaints. After inhalation:

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. After eye contact:

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects: Dizziness

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

CO2, extinguishing powder or water spray. Fight larger fires with water spray. **Extinguishing agents:**

Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: SAFETY GREEN (SOLVENT)

Protective equipment for

firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Methods and material for

Use respiratory protective device against the effects of fumes/dust/aerosol.

containment and cleaning up: Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) | Short-term value: 1000 ppm (EX)

142-82-5 heptane

PEL (USA) Long-term value: 2000 mg/m³, 500 ppm REL (USA) Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm *15-min

TLV (USA) Short-term value: 500 ppm Long-term value: 400 ppm

67-63-0 Isopropyl Alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm REL (USA) Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm

TLV (USA) Short-term value: 400 ppm Long-term value: 200 ppm

BEI, A4

Ingredients with biological limit values:

67-63-0 Isopropyl Alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use. Avoid contact with the skin.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Nitrile gloves.

Hand protection:

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Aromatic Odor: Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. -44.5 °C (-48.1 °F) **Boiling point:**

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: SAFETY GREEN (SOLVENT)

-19 °C (-2.2 °F) Flash point: Extremely flammable. Flammability (solid, gas):

Decomposition temperature: Not determined.

Product is not self-igniting. Auto igniting:

In use, may form flammable/explosive vapour-air mixture. Danger of explosion:

1.7 Vol % Lower Explosion Limit: Upper Explosion Limit: 10.9 Vol % Not determined. Vapor pressure:

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Viscosity: Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures. Not fully evaluated.

Chemical stability: Possibility of hazardous reactions:

No dangerous reactions known.

Incompatible materials: No further relevant information available. No dangerous decomposition products known. Hazardous decomposition:

11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 Isopropyl Alcohol

LD50 4,570 mg/kg (rat) Oral 13,400 mg/kg (rab) Dermal LD50 Inhalative LC50/4 h 30 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: Irritant to skin and mucous membranes.

Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

Toxic for fish Remark:

Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable

1950 Aerosols, ENVIRONMENTALLY HAZARDOUS **ADR**

Transport hazard class(es):

2.1 Gases Class

Symbol (fish and tree) Marine pollutant: Special precautions for user: Warning: Gases

EMS Number: F-D,S-Ŭ

Packaging Group:

(Contd. on page 4)

D

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: SAFETY GREEN (SOLVENT)

UN "Model Regulation": UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS (Contd. of page 3)

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

67-63-0 Isopropyl Alcohol

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadían Domestic Substances List All ingredients are listed or exempted.

(DSL): Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

1333-86-4 Carbon black

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

16 Other information

142-82-5 heptane

Contact: Regulatory Affairs