Printing date 01/25/2024 Revised On 01/25/2024

### 1 Identification of the substance and manufacturer

Trade name: **PBE 1K CLEAR** 0000201690 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:** 

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Eye Irritation 2A H319 Causes serious eye irritation. Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Carcinogenicity 1B H350 May cause cancer.

H336 May cause drowsiness or dizziness. Specific Target Organ Toxicity - Single Exposure 3

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms** 







GHS02 GHS04 GHS07 GHS08

Signal word Danger

**Hazard statements** Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell. Specific treatment (see on this label).

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Chomical Boootiphon.	The product is a mixture of the substances herea below with horniazar.	
Dangerous components:		
115-10-6 dimethyl ether		25-50%
67-64-1 Acetone		15-25%
123-86-4 butyl acetate		10-15%
108-65-6 PM acetate		5-10%
78-93-3 methyl ethyl ketone		≥5-<10%
628-63-7 pentyl acetate		1-5%
80-62-6 methyl methacrylate		≥0.2-<1%
64742-82-1 Naphtha (petroleum), hyd	rodesulfurized heavy	0.14%

#### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After eye contact:

(Contd. on page 2)

(Contd. of page 1)

**Safety Data Sheet** 

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: PBE 1K CLEAR

After swallowing:

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

Rinse mouth with water. Do not induce vomiting.

Dizziness

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Methods and material for containment and cleaning up:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

	controls/personal protection				
Components	Components with limit values that require monitoring at the workplace:				
115-10-6 dimethyl ether					
WEEL (USA)	Long-term value: 1000 ppm				
67-64-1 Acet	one				
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm				
REL (USA)	Long-term value: 590 mg/m³, 250 ppm				
TLV (USA)	Short-term value: 500 ppm				
	Long-term value: 250 ppm A4, BEI				
123-86-4 butyl acetate					
PEL (USA)	Long-term value: 710 mg/m³, 150 ppm				
REL (USA)	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm				
TLV (USA)	Short-term value: 150 ppm Long-term value: 50 ppm				
108-65-6 PM					
	Long-term value: 50 ppm				
	hyl ethyl ketone				
PEL (USA)	Long-term value: 590 mg/m³, 200 ppm				
REL (USA)	Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm				
TLV (USA)	Short-term value: 300 ppm Long-term value: 200 ppm BEI				
628-63-7 per					
PEL (USA)	Long-term value: 525 mg/m³, 100 ppm				
REL (USA)	Long-term value: 525 mg/m³, 100 ppm				
TLV (USA)	Short-term value: 100 ppm Long-term value: 50 ppm				
80-62-6 meth	hyl methacrylate				
PEL (USA)	Long-term value: 410 mg/m³, 100 ppm				
REL (USA)	Long-term value: 410 mg/m³, 100 ppm				
TLV (USA)	Short-term value: 100 ppm				
	Long-term value: 50 ppm DSEN, A4				
	(Contd. on page 3)				

(Contd. of page 2)

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: PBE 1K CLEAR

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

78-93-3 methyl ethyl ketone

BEI (USA) 2 mg/L

Medium: urine Time: end of shift

Parameter: Methyl ethyl ketone (nonspecific)

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

#### 9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. -24 °C (-11.2 °F) **Boiling point:** -19 °C (-2.2 °F) Flash point: Extremely flammable. Flammability (solid, gas):

**Decomposition temperature:** Not determined.

**Auto igniting:** Product is not self-igniting.

**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit:3 Vol %Upper Explosion Limit:18.6 Vol %Vapor pressure:Not determined.

**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)

Vapor density

Evaporation rate
Partition coefficient: n-octonal/water: Not determined.

Solubility:
Viscosity:

Not determined.
Not determined.
Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

**Conditions to avoid:**No decomposition if used according to specifications.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

#### 11 Toxicological information

LD/LC50 values that	t are relevant	tor cl	assification:

## 115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

123-86-4 butyl acetate

Oral LD50 14,000 mg/kg (rat) Inhalative LC50/4 h >21 mg/l (rat)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

(Contd. on page 4)

(Contd. of page 3)

# Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: PBE 1K CLEAR

78-93-3 methyl ethyl ketone

Oral LD50 3,300 mg/kg (rat) LD50 5,000 mg/kg (rbt) Dermal

628-63-7 pentyl acetate

LD50 6,500 mg/kg (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

Sénsitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: No further relevant information available. No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be

disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

**UN-Number** UN1950 DOT UN1950

DOT Aerosols, flammable **ADR** 1950 Aerosols

Transport hazard class(es):

Class 2.1 Gases Special precautions for user: Warning: Gases

F-D,S-Ŭ EMS Number:

**Packaging Group:** 

**UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

**Toxic Substances Control Act** 

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. Comission (CPSC):

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

67-64-1 Acetone

78-93-3 methyl ethyl ketone Τ

16 Other information

Contact: Regulatory Affairs