

Safety Data Sheet

Printing date 01/17/2024

Revised On 01/17/2024

1 Identification of the substance and manufacturer

Trade name: GOLD (METALLIC)
Product code: 0000980005
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com
Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.
 Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.
 Skin Irritation 2 H315 Causes skin irritation.
 Eye Irritation 2A H319 Causes serious eye irritation.
 Toxic to Reproduction 1B H360 May damage fertility or the unborn child.
 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.
 Causes serious eye irritation.

Precautionary statements

May damage fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

74-98-6	propane	15-25%
67-64-1	Acetone	15-25%
108-88-3	Toluene	≥15-<20%
106-97-8	n-butane	10-15%
110-19-0	Isobutyl Acetate	10-15%
86376-49-0	Brass Powder (Alloy)	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Immediately wash with water and soap and rinse thoroughly.
 Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 2)

Safety Data Sheet

Printing date 01/17/2024

Revised On 01/17/2024

Trade name: GOLD (METALLIC)

(Contd. of page 1)

After swallowing: Rinse out mouth and then drink plenty of water.
Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects: Dizziness

Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up: Ensure adequate ventilation.
Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.
Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****74-98-6 propane**

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) see Appendix F Minimal oxygen content (D, EX)

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm

REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 500 ppm
Long-term value: 250 ppm
A4, BEI

108-88-3 Toluene

PEL (USA) Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shift

REL (USA) Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV (USA) Long-term value: 20 ppm
BEI, OTO, A4

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 1000 ppm
(EX)

110-19-0 Isobutyl Acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm

REL (USA) Long-term value: 700 mg/m³, 150 ppm

TLV (USA) Short-term value: 150 ppm
Long-term value: 50 ppm

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA) 25 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

(Contd. on page 3)

Safety Data Sheet

Printing date 01/17/2024

Revised On 01/17/2024

Trade name: GOLD (METALLIC)

(Contd. of page 2)

108-88-3 Toluene

BEI (USA) 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.
 Immediately remove all soiled and contaminated clothing.
 Wash hands after use.
 Store protective clothing separately.
 Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.

Eye protection:

The glove material must be impermeable and resistant to the substance.
 Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.
pH-value: Not determined.
Melting point/Melting range Undetermined.
Boiling point: -44 °C (-47.2 °F)
Flash point: -19 °C (-2.2 °F)
Flammability (solid, gas): Extremely flammable.
Decomposition temperature: Not determined.
Auto igniting: Product is not self-igniting.
Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit: 1.7 Vol %
Upper Explosion Limit: 10.9 Vol %
Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapor density Not determined.
Evaporation rate Not applicable.
Partition coefficient: n-octanol/water: Not determined.
Solubility: Not determined.
Viscosity: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

110-19-0 Isobutyl Acetate

Oral LD50 4,763 mg/kg (rbt)

Information on toxicological effects: No data available.

Skin effects: No irritant effect.

Eye effects: No irritating effect.

(Contd. on page 4)

Safety Data Sheet

Printing date 01/17/2024

Revised On 01/17/2024

Trade name: GOLD (METALLIC)

Sensitization: No sensitizing effects known.

(Contd. of page 3)

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Remark: Toxic for fish
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950
DOT UN1950
DOT UN1950
ADR Aerosols, flammable
Transport hazard class(es): 1950 Aerosols
Class 2.1 Gases
Marine pollutant: Yes
Symbol (fish and tree)
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Packaging Group: --
UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 | Toluene

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 | Toluene

EPA:

67-64-1 | Acetone

I

110-19-0 | Isobutyl Acetate

D

16 Other information

Contact: Regulatory Affairs