





BRAAP DRY MOLY LUBE

#BW16-305

A quick-drying, gray film that provides superior lubrication under extreme pressures and a broad temperature ranges. Excellent adhesion, oil free, and protects against seizing, fretting, and galling. Provides excellent antiwear protection for cutting and forming tools.

Suggested Uses:

Dust free lubricant for pre-assembly and production Chains and sprockets Gasket and stop-off coating Rubber mold release Machine tool slides Joints, bushings, and latches **Packaging:**

UPC Code043281009331Cans per case6Shipping weight per case9 lbs.Container16 fluid ounce canLabel weight12 ounces (340 grams)Shipping Classificationlimited quantity, UN 1950Hazard Class2.1

Properties:

Cleanup Lacquer thinner Flammability **Extremely Flammable** Flash point -4F Specific Gravity 0.80 Solids Content 3% VOC content 47%, can't exceed 50% HAPs content 7% 40-90F Storage Temperature 40-100F Application Temperature Molybdenum Disulfide Active Ingredient Lubricity Rating Excellent Appearance Black Operating Speed 2000+ RPM High Temperature Resistence 600₀ F Low Temperature Resistence -1000 F Heavy Load Capability Yes Shelf life Guaranteed for 2 years

Dry Time:

Not Applicable

Gloss:

None



12-2-2021

917 Crosby Avenue • Sycamore, Illinois 60178-1394 Phone: 800-435-4482 or 815-895-9101 Fax: 800-343-4258 or 815-895-8475 Web Site: www.seymourpaint.com