Printing date 01/25/2024 Revised On 01/25/2024

1 Identification of the substance and manufacturer

Trade name: **EXTERIOR DETAILER**

0000200026 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

Emergency telephone number: 1-800-255-3924

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Additional information: GHS Hazard pictograms

Signal word Warning

Contains gas under pressure; may explode if heated. **Hazard statements** Protect from sunlight. Store in a well-ventilated place. **Precautionary statements**

3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description:

Dangerous components:		
	Mineral Spirits	25-50%
74-98-6	propane	5-10%
106-97-8	n-butane	1-5%
8042-47-5	White mineral oil, petroleum	1-5%
7632-00-0	sodium nitrite	0.2-1%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

Rinse opened eye for several minutes under running water. After eye contact:

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

No further relevant information available. Special hazards:

Protective equipment for

firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective

equipment and emergency procedures:

Methods and material for

Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material. containment and cleaning up:

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: EXTERIOR DETAILER

(Contd. of page 1)

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 1000 ppm

(EX)

Wash hands after use. Hygienic protection:

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In Breathing equipment: cases where short and/or long term overexposure exists, a NIOSH approved respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile aloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Not required.

9 Physical and chemical properties

Appearance: Aerosol. Aromatic Odor: Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. **Boiling point:** -44.5 °C (-48.1 °F) Flash point: -19 °C (-2.2 °F) **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: Not determined. Not determined. Lower Explosion Limit: Upper Explosion Limit: Not determined. Vapor pressure: Not determined.

Between 0.77 and 0.85 (Water equals 1.00) Relative Density:

Not determined. Vapor density Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Not determined. Viscosity:

Water: 54.5 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

No dangerous reactions known. Possibility of hazardous reactions:

No further relevant information available. Incompatible materials: Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: EXTERIOR DETAILER

Other adverse effects: No further relevant information available. (Contd. of page 2)

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 UN1950 DOT

ADR 1950 AEROSOLS

Transport hazard class(es):

Class 2.2 Gases Warning: Gases Special precautions for user: EMS Number: F-D.S-Ŭ

Packaging Group:

UN "Model Regulation": UN 1950 AEROSOLS, 2.2

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. Comission (CPSC):

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

None of the ingredients is listed.

16 Other information

Contact: Regulatory Affairs