1 Identification of the substance and manufacturer

Trade name: Product code: Recommended use: Uses advised against: Manufacturer/Supplier: Emergency telephone number:	GLOSS LIGHT BLUE 0000980037 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com 1-800-255-3924	Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com	
2 Horord(a) identification			
2 Hazard(s) identification	het we		
Classification of the substance or m			
Flammable Aerosols 1	H222 Extremely flammable aerosol.	we lead a if the actual	
Gases under Pressure - Liquefied gas	H280 Contains gas under pressure; may ex H319 Causes serious eye irritation.	xpioue il nealeu.	
Eye Irritation 2A Carcinogenicity 2	H351 Suspected of causing cancer. Route	of exposure: Inhalation	
Toxic to Reproduction 1B	H360 May damage fertility or the unborn ch		
Specific Target Organ Toxicity - Single		ind.	
	ted Exposure 2 H373 May cause damage to organs throug	h prolonged or repeated exposure	
Additional information:		··· p········	
GHS Hazard pictograms	$ \land \land$		
	GHS02 GHS04 GHS07 GHS08		
Signal word	Danger		
Hazard statements	Extremely flammable aerosol.		
	Contains gas under pressure; may explode if heated.		
	Causes serious eye irritation. Suspected of causing cancer. Route of exposure: Inhalatio	'n	
	May damage fertility or the unborn child.	ni.	
	May cause drowsiness or dizziness.		
	May cause damage to organs through prolonged or repeat Obtain special instructions before use.	ed exposure.	
Precautionary statements	Keep away from heat/sparks/open flames/hot surfaces N	lo smoking	
	Do not spray on an open flame or other ignition source.	-	
	Pressurized container: Do not pierce or burn, even after us	se.	
	Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.		
	Use only outdoors or in a well-ventilated area.		
	Wear protective gloves/protective clothing/eye protection/f	ace protection.	
	IF INHALED: Remove person to fresh air and keep comfor		
	If in eyes: Rinse cautiously with water for several minute easy to do. Continue rinsing.	s. Remove contact lenses, it present and	
	Call a poison center/doctor if you feel unwell.		
	If eye irritation persists: Get medical advice/attention.		
	Store in a well-ventilated place. Store locked up.		
	Protect from sunlight. Do not expose to temperatures exce	eding 50°C/122°F.	
	Dispose of contents/container in accordance with local/reg	ional/national/international regulations.	
3 Composition/information on ingredients			

on/information on ingre nho

	Description:	This product is a mixture of the substances listed below with nonhazardous additions.	
Dangerous components:			
67-64-1	Acetone		25-50%
	propane		15-25%
64742-89-8	VM&P Naphtha		10-15%
106-97-8	n-butane		10-15%
64742-47-8	Mineral Spirits		5-10%
108-88-3	Toluene		1-5%
13463-67-7	titanium dioxide		1-5%
67-63-0	Isopropyl Alcohol		1-5%

- **4 First-aid measures**
 - After inhalation: After skin contact: After eye contact:

Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 2)

Safety Data Sheet

Printing date 01/17/2024

Revised On 01/17/2024

ade name: GLOSS LIGHT BLUE	
After swallowing:	(Contd. of page Rinse out mouth and then drink plenty of water.
-	Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness
Indication of any immediate medi attention needed:	cal No further relevant information available.
5 Fire-fighting measures	
Extinguishing agents: Special hazards:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.
Protective equipment for	
firefighters:	A respiratory protective device may be necessary.
6 Accidental release measures	
Personal precautions, protective equipment and emergency	
procedures:	Wear protective equipment. Keep unprotected persons away.
Methods and material for	Use respiratory protective device against the effects of fumes/dust/aerosol.
containment and cleaning up:	Ensure adequate ventilation. Dispose contaminated material as waste according to section 13.
	Dispose contaminated material as waste according to section 13.
7 Handling and storage	
Precautions for safe handling	Use only in well ventilated areas. Keep away from sources of heat and direct suplight. Do not warehouse in subfreezing condition
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing condition Store locked up.
Long-term value: 250 p	nm
A4, BEI 74-98-6 propane	
A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 REL (USA) Long-term value: 1800	mg/m³, 1000 ppm mg/m³, 1000 ppm
A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 REL (USA) Long-term value: 1800 TLV (USA) see Appendix F Minima	mg/m³, 1000 ppm mg/m³, 1000 ppm
A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 REL (USA) Long-term value: 1800 TLV (USA) see Appendix F Minima 106-97-8 n-butane	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX)
A4, BEI74-98-6 propanePEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm
A4, BEI74-98-6 propanePEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm
A4, BEI74-98-6 propanePEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)Karter	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm
A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 REL (USA) Long-term value: 1800 TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) REL (USA) Long-term value: 1900 TLV (USA) Short-term value: 1000 (EX) 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 p Ceiling limit value: 300; Ceiling limit value: 300;	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm
A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 REL (USA) Long-term value: 1800 TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) REL (USA) Long-term value: 1900 TLV (USA) Short-term value: 1000 (EX) 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 560 m	mg/m ³ , 1000 ppm mg/m ³ , 1000 ppm I oxygen content (D, EX) mg/m ³ , 800 ppm ppm 500* ppm shift ng/m ³ , 150 ppm ng/m ³ , 100 ppm
A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 REL (USA) Long-term value: 1800 TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) REL (USA) Long-term value: 1900 TLV (USA) Short-term value: 1000 (EX) 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 200 p Ceiling limit value: 375 m Long-term value: 200 p REL (USA) Long-term value: 200 p BEI, OTO, A4 67-63-0 Isopropyl Alcohol	mg/m³, 1000 ppm mg/m³, 1000 ppm l oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm ng/m³, 100 ppm m
A4, BEI 74-98-6 propane PEL (USA) Long-term value: 1800 REL (USA) Long-term value: 1800 TLV (USA) see Appendix F Minima 106-97-8 n-butane REL (USA) REL (USA) Long-term value: 1900 TLV (USA) Short-term value: 1000 (EX) 108-88-3 Toluene PEL (USA) PEL (USA) Long-term value: 200 p Ceiling limit value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 300; *10-min peak per 8-hr s REL (USA) Short-term value: 375 m TLV (USA) Long-term value: 20 pp BEI, OTO, A4 67-63-0 Ispropyl Alcohol PEL (USA) Long-term value: 280 m	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm ng/m³, 150 ppm m
A4, BEI74-98-6 propanePEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)I08-88-3 ToluenePEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 560 n Long-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Ispropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 980 m	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm ng/m³, 100 ppm m
A4, BEI74-98-6 propanePEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1900TLV (USA)Short-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 560 n Long-term value: 375 mTLV (USA)Long-term value: 20 pBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 980 mREL (USA)Short-term value: 980 mTLV (USA)Short-term value: 200 pDet (USA)Short-term value: 200 pTLV (USA)Short-term value: 200 pTLV (USA)Short-term value: 200 pCeiling limit value: 200 pShort-term value: 200 p	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm ng/m³, 150 ppm m
A4, BEI74-98-6 propanePEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)108-88-3 ToluenePEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 980 mTLV (USA)Short-term value: 200 pBEI, OTO, A4Short-term value: 200 pBEI, A4Ingredients with biological limit v	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm mg/m³, 150 ppm mg/m³, 400 ppm mg/m³, 400 ppm
A4, BEI74-98-6 propanePEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)108-88-3 ToluenePEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Long-term value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 980 mTLV (USA)Short-term value: 200 pBEI, OTO, A4Short-term value: 200 pBEI, A4Ingredients with biological limit vIngredients with biological limit v	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm mg/m³, 150 ppm mg/m³, 400 ppm mg/m³, 400 ppm
A4, BEI74-98-6 propanePEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)(EX)108-88-3 ToluenePEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 560 n Long-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 1225 Long-term value: 980 mTLV (USA)Short-term value: 200 pBEI, A4Ingredients with biological limit vBEI (USA)25 mg/L Medium: urine	mg/m³, 1000 ppm mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm shift ng/m³, 150 ppm mg/m³, 150 ppm mg/m³, 400 ppm mg/m³, 400 ppm
A4, BEI74-98-6 propanePEL (USA)Long-term value: 1800REL (USA)Long-term value: 1800TLV (USA)see Appendix F Minima106-97-8 n-butaneREL (USA)REL (USA)Long-term value: 1900TLV (USA)Short-term value: 1000(EX)(EX)108-88-3 ToluenePEL (USA)PEL (USA)Long-term value: 200 pCeiling limit value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 300; *10-min peak per 8-hr sREL (USA)Short-term value: 375 mTLV (USA)Long-term value: 20 ppBEI, OTO, A467-63-0 Isopropyl AlcoholPEL (USA)Long-term value: 980 mREL (USA)Short-term value: 1225 Long-term value: 980 mTLV (USA)Short-term value: 200 pBEI, A4Ingredients with biological limit v67-64-1 AcetoneBEI (USA)BEI (USA)25 mg/L	mg/m³, 1000 ppm I oxygen content (D, EX) mg/m³, 800 ppm ppm 500* ppm hilf f f g/m³, 150 ppm ng/m³, 150 ppm mg/m³, 100 ppm mg/m³, 400 ppm ng/m³, 400 ppm

F

Revised On 01/17/2024

Trade name: GLOSS LIGHT BLUE

	(Contd. of page 2)	
108-88-3 Toluene		
BEI (USA) 0.02 mg/L		
	Medium: blood Time: prior to last shift of workweek	
Parameter: Toluene		
0.03 mg/L Medium: urine		
Time: end of shift		
Parameter: Toluene		
0.3 mg/g creatinine	0.3 mg/g creatining	
Medium: urine		
Time: end of shift		
Parameter: o-Cresol with h	nydrolysis (background)	
67-63-0 Isopropyl Alcohol		
BEI (USA) 40 mg/L Medium: urine		
Time: end of shift at end of	f workweek	
Parameter: Acetone (back		
Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use.	
	Immediately remove all soiled and contaminated clothing. Wash hands after use.	
	Store protective clothing separately.	
	Avoid contact with the eyes and skin.	
Breathing equipment:	Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In	
Breating equipment.	cases where short and/or long term overexposure exists, a NIOSH approved respirator should be	
	worn. If you suspect overexposure conditions exist, please consult an authority on chemical	
Hand protection.	hygiene.	
Hand protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.	
Eye protection:	Tightly sealed goggles	
0 Rhusiaal and shamiaal menoritie		
9 Physical and chemical propertie	S Aerosol.	
Appearance: Odor:	Aromatic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range		
Boiling point:	-44 °C (-47.2 °F)	
Flash point:	-19 °C (-2.2 °F)	
Flammability (solid, gas):	Extremely flammable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not self-igniting.	
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture. 1.7 Vol %	
Lower Explosion Limit: Upper Explosion Limit:	10.9 Vol %	
Vapor pressure:	Not determined.	
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)	
Vapor density	Not determined.	
Evaporation rate Partition coefficient: n-octonal/wate	Not applicable.	
Solubility: Viscosity:	Not determined. Not determined.	
Water:	0.0 %	
10 Stability and reactivity		
Reactivity: Conditions to avoid:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing	
	temperatures.	
Chemical stability:	Not fully evaluated.	
Possibility of hazardous reactions:	No dangerous reactions known.	
Incompatible materials: Hazardous decomposition:	No further relevant information available. No dangerous decomposition products known.	
114241 4043 4600111003111011.		

Safety Data Sheet

Printing date 01/17/2024

Trade name: GLOSS LIGHT BLUE

Revised On 01/17/2024

(Contd of r 3)

Page 4/5

	(Contd. of page 3)		
11 Toxicological information			
LD/LC50 values that are relevant for classification:			
13463-67-7 titanium dioxide			
Oral LD50 >20,000 mg/kg	(rat)		
Dermal LD50 >10,000 mg/kg			
Inhalative LC50/4 h >6.82 mg/l (rat)			
67-63-0 Isopropyl Alcohol			
Oral LD50 4,570 mg/kg (ra	t)		
Dermal LD50 13,400 mg/kg (r			
Inhalative LC50/4 h 30 mg/l (rat)	,		
Information on toxicological effects Skin effects: Eye effects: Sensitization:	s: No data available. No irritant effect. Irritating effect. No sensitizing effects known.		
42 Feelerical information			
12 Ecological information	llemendeur ferunden de neternet inte derive		
Aquatic toxicity: Persistence and degradability: Other information:	Hazardous for water, do not empty into drains. The product is degradable after prolonged exposure to natural weathering processes. This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.		
Bioaccumulative potential: Mobility in soil: Other adverse effects:	No further relevant information available. No further relevant information available. No further relevant information available.		
13 Disposal considerations Dispose of in accordance with local, disposed of responsibly. Do not heat Recommendation: Recommended cleansing agent:	state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be or cut empty containers with electric or gas torches. Completely empty cans should be recycled. Water, if necessary with cleansing agents.		
14 Transport information			
UN-Number DOT	UN1950 UN1950		
DOT	Aerosols, flammable		
ADR	1950 Aerosols		
Transport hazard class(es):			
Class Marine pollutenti	2.1 Gases No		
Marine pollutant: Special precautions for user:	Warning: Gases		
EMS Number:	F-D,S-Ŭ		
Packaging Group:			
UN "Model Regulation":	UN1950, Aerosols, 2.1		
15 Regulatory information			
SARA Section 355 (extremely haza			
None of the ingredients in this produc			
SARA Section 313 (Specific toxic c 108-88-3 Toluene	nemical listings):		
67-63-0 Isopropyl Alcohol			
Toxic Substances Control Act			
(TSCA): Canadian Domestic Substances Lis (DSL):	All hazardous ingredients are found on the inventory list of substances. st All ingredients are listed or exempted.		
Consumer Product Safety	An ingrouonia are insteu or exempteu.		
Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.		
California Proposition 65 chemical			
California Proposition 65 chemical 13463-67-7 titanium dioxide			
California Proposition 65 chemical			
California Proposition 65 chemical 13463-67-7 titanium dioxide 100-41-4 ethyl benzene Prop 65 chemicals known to cause			
California Proposition 65 chemical 13463-67-7 titanium dioxide 100-41-4 ethyl benzene	s known to cause cancer:		

Revised On 01/17/2024

Page 5/5

Trade name: GLOSS LIGHT BLUE		
		(Contd. of page 4)
EPA:		
67-64-1 Acetone		1
16 Other information		
Contact:	Regulatory Affairs	