

## WW-732 SERIES VINYL ELECTRICAL TAPE

DESCRIPTION			FEATURES		
WW-732 is a superior high-performance vinyl electrical tape ideal for splicing, insulating and cable marking. For indoor and outdoor use.		<ul> <li>Superior elasticity and adhesion</li> <li>All-weather performance</li> <li>Excellent break strength</li> <li>Flame-retardant</li> <li>Rated up to 600V</li> <li>UV, abrasion and corrosion resistant</li> </ul>			
	BACKING	ADHESIVE	COLORS	STANDARD SIZES (WIDTH X LENGTH)	PART NUMBERS
		Vinyl Rubber based (BN) Bro (GN) Gre (GY) Gre (CR) Orau (PK) Pir (RD) Re (VT) Vin (WT) Wh	Black	1.5" x 40' (38mm x 13.4m)	WW-732-15
MATERIALS	Vinyl		(BL) Blue (BN) Brown (GN) Green (GY) Gray (OR) Orange (PK) Pink (RD) Red (VT) Violet (WT) White (YL) Yellow	.75" x 60' (19mm x 18.28m)	WW-732 WW-732-BL WW-732-BN WW-732-GN WW-732-GY WW-732-OR WW-732-PK WW-732-PK WW-732-VT WW-732-VT WW-732-VT WW-732-WT WW-732-YL
TECHNICAL PROPERTIES	CHARACTERISTIC	TYPICAL VALUE		TEST METHOD	
	Thickness (mils)	7		ASTM D 1000	
	Adhesion to steel (oz/in)	33		ASTM D 1000	
	Adhesion to backing (oz/in)	33		ASTM D 1000	
	Elongation at break (%)	286		ASTM D 1000	
	Dielectric strength (V/mil)	1289		ASTM D 1000	
	Operating temp.	0°F to 221°F, -18°C to 105°C		ASTM D 1000	
	Certifications	UL 510, CSA C22.2			
RECOMMENDED USES		STORAGE		SHELF LIFE	

RECOMMENDED USES	STORAGE	SHELF LIFE	
Specifically designed for insulating, splicing and cable marking. For indoor and outdoor use.	Product should be stored in humidity- controlled, dry conditions between 50°F and 73°F (10°C and 23°C). Relative humidity should be less than 65%	24 months from date of manufacture.	

Data in table represents average test results and are not to be used for specification purpose. Users should test the products' suitability for their intended use themselves.

LIMITED WARRANTY: NSI Industries LLC warrants that each of its products will be free from material and manufacture defects at the date of shipment (unless specified otherwise). NSI Industries LLC makes or gives no warranty to the distributor, its customers, or the product's end user regarding the product's merchantability and/or suitability for their/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proven to be defective, NSI Industries sole obligation and buyer's exclusive remedy shall be through the distributor, at NSI Industries' discretion, to replace, repair, or refund the product proved to be defective within the time period specified above. EXCEPT AS EXPRESSLY SET FORTH HEREIN, NSI INDUSTRIES MAKES OR GIVES NO OTHER WARRANTIES, EXPRESSED OR IMPLIED. Except where prohibited by law, NSI Industries LLC will not be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products.

