

WW-HW SERIES HARNESS WRAP

DESCRIPTION			FEATURES		
strength for the harnessing	ape is vinyl-backed 5 mil tape with e and bundling of cables. It is best us applications that require the securin	 Vinyl back Good adh Good elor Great for s 	esion		
MATERIALS	BACKING	ADHESIVE	COLOR	STANDARD SIZE (WIDTH X LENGTH)	PART NUMBER
	Vinyl	Rubber based	Black	.75" x 60' (19mm x 18.3m)	WW-HW-75
TECHNICAL PROPERTIES	CHARACTERISTIC	TYPICAL VALUE		TEST METHOD	
	Thickness (mils)	5		ASTM D 1000	
	Breaking strength (lbs/in)	11		ASTM D 1000	
		125			
	Elongation at break (%)	125		ASTM D 100	0
PROPERTIES	Elongation at break (%) Adhesion to steel (oz/in)	125		ASTM D 100 ASTM D 100	
					0
	Adhesion to steel (oz/in)	12		ASTM D 100	0
PROPERTIES	Adhesion to steel (oz/in) Adhesion to backing (oz/in)	12	GE	ASTM D 100 ASTM D 100	0 0 0 0

Data in table represents average test results and are not to be used for specification purpose. Users should test the products' suitability for their intended use themselves.

LIMITED WARRANTY: NSI Industries LLC warrants that each of its products will be free from material and manufacture defects at the date of shipment (unless specified otherwise). NSI Industries LLC makes or gives no warranty to the distributor, its customers, or the product's end user regarding the product's merchantability and/or suitability for their/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proven to be defective, NSI Industries sole obligation and buyer's exclusive remedy shall be through the distributor, at NSI Industries' discretion, to replace, repair, or refund the product proved to be defective within the time period specified above. EXCEPT AS EXPRESSLY SET FORTH HEREIN, NSI INDUSTRIES MAKES OR GIVES NO OTHER WARRANTIES, EXPRESSED OR IMPLIED. Except where prohibited by law, NSI Industries LLC will not be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products.

In original packaging, placed in a horizontal

position, covered, between 5°C and 35°C.



For harnessing, bundling and securing cables

60 months from date of manufacture.