INSERT CARD

Card Part Number: 100022C Tool Part Number: 100022 Clamshell Part Number: 9066 Card Size: 64x203.2 mm (2.52"x 8")

Warranty: N/A

Finish: 3/16 radius corner Stock: Postcard 16 PT. C2S Finish: Round corners

External Ground, 50 pcs EZ-RJ45° Cat5/6 Shielded



P/N 100022C

FRONT = CMYK

Platinum Tools We Make Connections EZ!

REC®N Test Set



VDV MapMaster 2.0



Adds length measurement to Voice/Data/Video testing P/N T129



Professional Electrician's Scissors P/N 10525C



CCS-6 Cable Cutter P/N 10514

visit platinumtools.com to see all of our products



Made in U.S.A.

P/N 100022C



EZ-R.J45® Cat5/6 Shielded External **Ground Connector**

The Original EZ-RJ45 shielded CAT5/6 connector simplifies twisted pair terminations by allowing the wires to be inserted through the connector and out the front for EZ verification of wiring sequence. Applications with RF problems or grounding requirements usually specify to use shielded cable & shielded connectors.

- Max Outer Cable Diameter: 0.280" (7.11 mm)
- Max Insulation Diameter (Conductors): 0.040" (1.016 mm)
- Meets ANSI/EIA/TIA/TAA specs
- Solid or Stranded, 24 23 AWG
- UL Listed and RoHS3/ **FCC** compliant
- . 50 micron gold plated contacts

Crimp with P/Ns 100062, 100054, or 100004 EZ-RJ45 Crimp Tools



Shielded EZ-RJ45 Instructions

- 1. Strip 2" off the cable jacket, keeping foil intact.
- 2. Straighten wires, place in proper sequence.
- 3. Fold 5/8" of foil for Cat5e & 1" for Cat6 back over the jacket, drain wire can be included
- 4. Push down on ground device to clear entry way for cable.
- 5. Verify wiring sequence & cinch connector down on cable.
- 6. Push ground device back up and wrap around foil & cable.
- 7. Crimp with the EZ-RJPRO HD crimp tool.

△ WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

EZ-RJ45® is a registered trademark of Platinum Tools.

North Carolina, USA

platinumtools.com

BACK = 1 COLOR